



Raptor Line Interactive UPS



Overview

The Powercom UPS Raptor is the ultimate power solution from the Raptor Series. This powerful device seamlessly combines energy-saving features, full power protection, and a compact form factor to become your reliable partner for PCs and workstations.

Main Features

- Comprehensive power protection: Raptor offers full-range protection against critical situations like surges, overload, and short circuits, ensuring your critical systems stay safe.
- Automatic Voltage Regulator (AVR): Raptor's built-in AVR regulates fluctuating voltage, providing consistent power output and extending battery life.
- Green mode energy-saving feature: Raptor's Green mode prevents unnecessary energy waste during non-essential periods, maintaining efficient battery life and power consumption.
- Advanced Battery Management: Intelligent battery control ensures battery efficiency and lifespan.
- One-button Control: Raptor's user-friendly interface allows for functions like self-tests, mode changes, and power control, all achievable through one simple button.
- LED/LCD Status Display: Clear information about UPS current status is provided through distinct LED flash patterns and an LCD screen.
- Audio Alarm Warning: Receive immediate notifications of UPS status warnings through distinct audible alarms.
- UPSMON PRO APP Monitoring Support: Use UPSMON PRO and the accompanying app for remote monitoring, real-time status display, and user-friendly controls such as scheduled shutdowns, data logging, and self-diagnostics.
- Experience the future of power protection with the UPS RAPTOR 600VA. Elevate your power reliability, reduce energy waste, and gain control over your critical systems. Trust in Raptor's advanced features to keep your PCs and workstations running smoothly.

Model	Dimensions	Weight	Ship Dimensions	Ship Weight
RPT-600A RPT-600AP	100 x 278 x 143mm	4.3kg	147 x 329 x 227mm	4.8kg
RPT-800A RPT-800AP	100 x 278 x 143mm	4.8kg	147 x 329 x 227mm	5.3kg
RPT-1025AP	147 x 360 x 164mm	8.5kg	233 x 449 x 277mm	9.7kg
RPT-1500AP	147 x 360 x 164mm	10.1kg	233 x 449 x 277mm	11.3kg
RPT-2000AP	147 x 360 x 164mm	11.1kg	233 x 449 x 277mm	12.3kg

Distributed by:



www.accesscomms.com.au | sales@accesscomms.com.au

Specifications

	RPT-600A/AP	RPT-800A/AP	RPT-1025AP	RPT-1500AP	RPT-2000AP
Configuration					
Capacity (VA)	600VA	800VA	1025VA	1500VA	2000VA
Capacity (Watts)	360W	480W	615W	900W	1200W
Form	Tower type				
Input					
Voltage	100/110/120 VAC or 200/230/240 VAC				
Input voltage range	75 150 or 165-300 VAC				
Input frequency range	50 Hz / 60 Hz (Auto sensing)				
Output					
Waveform	Simulated sine wave				
Voltage	100/110/120 VAC or 220/230/240 VAC				
Frequency	50 Hz / 60 Hz ± 0.25 Hz				
Transfer time	2-4 ms (typical)				
Protection					
Full protection	Overload, surge, short circuit				
Telecommunication	RJ11 / RJ45 : AP model				
Battery					
Type	12V 7Ah	12V 7.2Ah	12V 7Ah	12V7 .2Ah	12V 9Ah
Quantity	1	1	2	2	2
Sealed Maintenance Free	Yes				
Typical Recharge Time	3-4 hour to 90%				
Management & Communication					
Indicator	LED indicator		LED or LCD		
Communication port	USB B type : AP model				
Physical					
Dimensions	100 x 278 x 143mm		147 x 360 x 164mm		
Weight	4.3kg	4.8kg	8.5kg	10.1kg	11.1kg
Shipping dimensions	147 x 329 x 227mm		233 x 449 x 277mm		
Shipping weight	4.8kg	5.3kg	9.7kg	11.3kg	12.3kg
Alarm					
Overload / Fault	Continuous beeping				
Battery mode	Beep every 2 seconds				
Low Battery	Beep every 0.5 second				

Environment	
Operating humidity	0-95% RH at 0-40°C (non condensing)
Audible noise	Less than 40 dB

* Specifications are subject to change without further notice.

* Specifications are for reference, please refer to information based on real product.